


# PLADUR® T-47 / T-60 HANGERS

02b01001EN - Rev. 10/2015




## DESCRIPTION

U-shaped hanger for continuous ceilings, built in low-carbon steel sheets, that have been hot-dip galvanised in a continuous line, for subsequent cold-forming. The core has a trapezoidal shape and its wings have a hollowed-out groove for assembly with the profiles, by pressing or turning. The combination of high-quality steel, a solid and thick surface layer and a production process based on cutting-edge profiling and stamping technology provides the Pladur® T-47 and T-60 Hangers with excellent anti-corrosion protection and great mechanical resistance.

## APPLICATIONS

Suitable for hanging the corresponding T-47 and T-60 profiles, using the threaded rod, to form part of the load-bearing structure of Pladur® Continuous Ceilings.

## PROFILE DESIGN



## TECHNICAL SPECIFICATIONS

FEATURE	VALUE	
	T-47 Hanger	T-60 Hanger
Type of steel	DX51D	
Lining	ZINC LAYER (Z140)	
Thickness (mm)	1.0	1.5
Internal width (x) (mm)	24.4	29.4
External width (h) (mm)	24.4	32.54
Internal length (l) (mm)	32.5	47.35
External length (L) (mm)	51.9	60.27
Height (a) (mm)	24.8	33.2
Approximate weight (kg/m)	0.04	0.06
Admissible load (kg)	40	75
Reaction to fire performance	A1 (Does not contribute to fire)	
Applicable regulations/standards	EN-13964 	

## PRESENTATION

### Packaging

	T-47 Hanger	T-60 Hanger
Units / Box	100	100
Boxes / Pallet	120	120

Central Offices and Factory in Valdemoro-Madrid  
 Laminated plasterboards, Transformations,  
 Profiles and Adhesive Compounds

This document is provided as a guideline only and refers to installations and applications based exclusively on the use of PLADUR® materials in accordance with the specifications contained herein. Any use or installation based on PLADUR® materials that does not follow the recommendations and parameters set out in this document must be confirmed with the Yesos Ibéricos S.A Technical Department first. PLADUR® is a registered trademark belonging to Yesos Ibéricos, S.A. Published July 2015. This publication is considered valid save for any typographic or transcription error. All rights reserved, including the incorporation of improvements or amendments.

## TOLERANCES

FEATURE	VALUE
Thickness	± 0.03 mm (T-47) ± 0.10 mm (T-60)
Internal width (x)	± 0.3 mm (T-47) +0.4 / -0 mm (T-60)
External width (h)	± 0.3 mm (T-47) ± 0.3 mm (T-60)
Height (a)	± 0.3 mm (T-47) ± 0.4 mm (T-60)
Internal length (l)	± 0.3 mm (T-47) ± 0.1 mm (T-60)
External length (L)	± 0.3 mm (T-47) ± 0.1 mm (T-60)

## INSTALLATION

- The regulations and laws applicable in the territories where the materials are installed must be followed at all times.
- For any queries regarding the recommendations from Yesos Ibéricos for the installation or for technical support, please write to [info@pladur.com](mailto:info@pladur.com).

## PRECAUTIONS

- We only guarantee the results obtained in our tests or predictions, as set out in our technical documentation, when the product is used in combination with other original Pladur® products (boards, profiles, compounds, screws and accessories).
- For detailed information on safety, please read the product safety data sheet.

## STORAGE & HANDLING

- Store horizontally, on a dry and flat surface, preferably protected from sunlight and rain.
- We recommend wearing mechanical protection gloves when handling the profiles, as advised in Standards EN 420 and EN 388.

Customer Service  
**+34 902 023 323**  
[info@pladur.com](mailto:info@pladur.com)  
[www.pladur.com](http://www.pladur.com)



**Pladur®**  
 Makes it a reality