

1. Name and identification code:

PLADUR DECOR N-10 BV	DECOR + AL- A-10 –EN 14190
PLADUR DECOR N-13 BV	DECOR + AL- A-13 –EN 14190

2. Name and manufacturer address:

PLADUR GYPSUM S.A.U.
Ctra. de Andalucía Km. 30,2 28343 Valdemoro (Madrid) – Spain

3. Intended use:

Use in modular ceilings

4. System of assessment and verification of constancy of performances: 3/4

5. Notified body:

Name and number	APPLUS /LGAI Technological Center, S.A. nº : 0370
Task performed	Test reaction to fire
Evaluation system	3
Document issued and date of issue	Exp. Nº 15/8956-657 m1 Fecha: 23-02-2017

6. Declared performance:

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire	B-s1, d0	EN 13501-1:2007+A1:2009
Stability of ceiling elements	NPD	NPD
Water vapour permeability	∞	EN 12524:2000
Flexural strength longitudinal		
Thickness 10 mm	≥400 N	EN 14190:2014
Thickness 13 mm	≥600 N	
Flexural strength transversal		
Thickness 10 mm	≥170 N	EN 14190:2014
Thickness 13 mm	≥210 N	
Thermal resistance	0,25	EN 12524:2000
Direct airborne sound insulation	See technical documentation	--
Impact resistance		
Acoustic absorption		

All essential characteristics described in the first column of this table correspond to those described in the standard EN 14190:2014.

The performance of the product identified in paragraph 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2.

Valdemoro 23rd April 2018